




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04L 12/58, H04M 3/50		A1	(11) International Publication Number: WO 99/03239
			(43) International Publication Date: 21 January 1999 (21.01.99)
(21) International Application Number: PCT/US98/13731		(81) Designated States: CA, MX, European patent (DE, FR, GB).	
(22) International Filing Date: 1 July 1998 (01.07.98)		Published With international search report.	
(30) Priority Data: 08/888,535 7 July 1997 (07.07.97) US			
(71) Applicant: AT & T CORP. [US/US]; 32 Avenue of the Americas, New York, NY 10013-2412 (US).			
(72) Inventor: HALL, Robert, J.; 79 Beech Avenue, Berkeley Heights, NJ 07922 (US).			
(74) Agents: DWORETSKY, Samuel, H. et al.; AT & T Corp., P.O. Box 4110, Middletown, NJ 07748 (US).			

(54) Title: ELECTRONIC MAIL MESSAGE NOTIFICATION METHOD AND APPARATUS

(57) Abstract

The present invention is a method and apparatus for notifying a recipient that an electronic mail (email) message addressed to the recipient has been received at an electronic mail messaging system. Responsive to an email messaging system receiving an email message addressed to a recipient, the email messaging system places an alert telephone call to the recipient. The alert telephone call indicates that the email message has been received. A notification device at the recipient's location detects the alert telephone call and indicates that the alert telephone call has been detected. The notification device comprises a detection circuit detecting an alert call placed in response to receipt of the email message and an indicator circuit indicating that the alert call has been detected. In one embodiment, the indicator circuit comprises a counter circuit counting a number of alert calls that have been detected and a display displaying the number of alert calls that have been detected.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Larvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

ELECTRONIC MAIL MESSAGE NOTIFICATION METHOD AND APPARATUS

Field of the Invention

5 The present invention relates to a system and method for notifying a recipient of an electronic mail message that the message has been received.

Background of the Invention

 Currently, a user of a consumer online service has no way of telling when there are unread electronic mail (email) messages present in the
10 user's account when the user is off-line. The user must periodically logon to the email messaging system to check for new email. The logon process may be rather lengthy, involving steps such as turning on a computer, waiting for the computer to boot, launching an application program, initiating a connection, and waiting for the connection to be made. Due to
15 the inconvenience of this process, many users logon infrequently, for example, once a day. Thus, the time it takes for an email message to be delivered to the recipient may be a day or more. This delay tends to diminish the usefulness of email and make it less likely that email will be used when a quicker response is desired.

20 A need arises for a technique by which the email message delivery delay time may be reduced. Such a reduction would result if a user was

notified of new email message soon after the message was received by the email messaging system. A need arises for a technique by which users of email messaging are notified of a new email message soon after the message is received by the email messaging system.

5 **Summary of the Invention**

The present invention is a method and apparatus for notifying a recipient that an electronic mail (email) message addressed to the recipient has been received at an electronic mail messaging system. The invention provides a simple and inexpensive way of notifying the recipient when
10 they should logon to retrieve an email message.

Responsive to an email messaging system receiving an email message addressed to a recipient, the email messaging system places an alert telephone call to the recipient. The alert telephone call indicates that the email message has been received. A notification device at the
15 recipient's location detects the alert telephone call and indicates that the alert telephone call has been detected.

The notification device comprises a detection circuit detecting an alert call placed in response to receipt of the email message and an indicator circuit indicating that the alert call has been detected. In one
20 embodiment, the indicator circuit comprises a counter circuit counting a

number of alert calls that have been detected and a display displaying the number of alert calls that have been detected.

Brief Description of the Drawings

The details of the present invention, both as to its structure and
5 operation, can best be understood by referring to the accompanying drawings, in which like reference numbers and designations refer to like elements.

Fig. 1 is a block diagram of a system including an email notification device **116**, according to the present invention.

10 Fig. 2 is a block diagram of one embodiment of a notification device **116**, according to the present invention.

Fig. 3a is a block diagram of a typical email recipient system configuration including a notification device, according to the present invention.

15 Fig. 3b is a block diagram of another typical email recipient system configuration including a notification device, according to the present invention.

Fig. 4a is a block diagram of an exemplary system, in which an automated notification process, according to the present invention, may be
20 implemented.

Fig. 4b is a flow diagram of an email notification process **450**, implemented in the system of Fig. 4a.

Detailed Description of the Invention

An electronic mail (email) notification device **116** of the present invention, and the system in which it operates, is shown in Fig. 1. An email sender **102** transmits an email message **104**, which is addressed to email recipient **106**, to email messaging system **108**. The email message may be sent over any conventional transmission medium, such as a local or wide area network, or the Internet. The email messaging system places the received email message in the inbox of the account belonging to email recipient **106**.

After the email sender **102** transmits the email message, he may then place an alert telephone call **110a** to email recipient **106** at a designated telephone number using the public switched telephone network (PSTN) **112**. Alternatively, after the email message has been placed in the inbox, the email messaging system **108** may place an alert telephone call **110b** to email recipient **106** at the designated telephone number using the PSTN **112**. The PSTN **112** completes the alert call to the telephone line **114** corresponding to the designated telephone number. Notification device **116** is connected to telephone line **114** and detects the ring signal of the alert call. Email sender **102** or email messaging system **108** allows the

call to ring a predetermined number of times, then terminates the call. Notification device **116** detects the call and determines that it is an alert call based on the number of rings. Notification device **116** then generates an indication **118** that an alert call has been detected for email recipient

5 **106**, thus notifying recipient **106** that an email message has arrived.

A block diagram of one embodiment of a notification device **116**, according to the present invention, is shown in Fig. 2. Notification device **116** detects each alert call which comes in on line **114**, which is a standard telephone line. Notification device **116** includes a well-known telephone

10 ring detector circuit **204**, which is connected to telephone line **114**. Ring detector **204** outputs a signal **206** that indicates that line **114** is ringing. Signal **206** is input to counter/comparator **208**, which counts each ring on line **114**. Once the call is detected to have terminated, such as by no ring detected for an interval of five seconds, counter/comparator **208** compares

15 the number of rings counted with a predefined target number of rings. When the number of rings equals, but does not exceed the predefined target number, counter comparator **208** outputs signal **210**, which indicates that an alert call has been received. This allows notification device **116** to distinguish alert calls from other types of calls that may come in on line

20 **114**. For example, the target number of rings may be set to one. When a call comes in on line **114**, ring detector **204** will detect each ring. After the

first ring, counter comparator **208** will detect that the target number of rings has been reached. If the call is not an alert call, line **114** will continue ringing. Counter/comparator **208** will detect that the preset number of rings has been exceeded and will not output signal **210**. If the
5 call is an alert call, the call will terminate, counter/comparator **208** will detect that the preset number of rings has not been exceeded, and will output signal **210**, which indicates that an alert call has been detected.

Signal **210** is input to counter circuit **212**, which counts the number of alert calls that have been received on line **204**. Counter circuit **212**
10 outputs a signal **214** to indicator **216** indicating the current count of alert calls. Indicator **216** displays the number of alert calls. When an alert call **110a** or **110b**, as shown in Fig. 1, which indicates that an email message is waiting, is received, the notification device indicates that the email message is waiting to the email recipient. After being notified, the
15 recipient may reset the count of alert calls using reset device **218**, which is typically a button or switch. Thus, counter **212** counts alert calls that have arrived since the last reset.

In another embodiment of the notification device, counter **212** is replaced by a simple latching device, which latches signal **210**. This
20 embodiment indicates only that one or more alert calls have been received, thus notifying that one or more email messages are waiting. The number

of alert calls is not displayed. The recipient may reset the notification device using reset device **218**.

Indicator **216** may be a visual display device or an audible indicator. In an embodiment in which the number of messages is displayed, the visual display device may be, for example, an alpha-numeric display device that directly displays the number of alert calls or a flashing light indicating the number of alert calls by its flashing pattern. In such an embodiment, an audible indicator may be a simple beeper, indicating the number of alert calls by its beeping pattern, or the audible indicator may be a speech synthesis device generating a spoken message indicating the number of alert calls waiting. Visual and audible indicators may both be present in one notification device.

Notification device **116** may be advantageously installed on any telephone line used by the email recipient. A typical configuration is shown in Fig. 3a. In this configuration, the recipient has a separate dedicated telephone line that is used to access the email messaging system. The typical email recipient has a computer system **302**, which is often a standard personal computer. The typical email recipient also has a conventional modem **304**, which is used to logon to the email messaging system in order to transmit and receive email messages. Both modem **304** and notification device **116** are connected to telephone line **114**.

Notification device **116** may include a conventional telephone line pass-through circuit, to allow convenient connection of the device to the telephone line and the modem. Generally, a typical email user initiates telephone calls to the email messaging system.

5 Another typical configuration is shown in Fig. 3b. In this configuration, the email recipient uses a single telephone line that is shared among several devices. For example, in addition to notification device **116** and modem **304**, a telephone set **306** and one or more additional telephone devices **308**, such as a telephone answering machine, a fax
10 machine, etc., are connected as well. Many of these devices include pass-through circuits, to facilitate connection of additional devices. Notification device **116** may be advantageously used in this configuration as long as the target number of rings is properly set to correspond to the number of rings of an alert call. As an example, in a typical configuration,
15 notification device **116** is set to respond to the number of rings of an alert call, for example, one ring, and device **308** may be set to respond to four rings. An incoming call, regardless of type, will ring on line **114**. If the call is an alert call, the call will ring once and then terminate. Notification device **116** will detect the alert call and indicate that an email message is
20 waiting. Device **308** will not respond to the call. If the call is not an alert call, the call will ring on line **114** more than once. Notification device **116**

will detect this situation and will not register the call as an alert call. As the call continues ringing, any person present may answer the call with telephone station 306, or after four rings, device 308 will respond by answering the call.

5 An exemplary system, in which an automated notification process, according to the present invention, may be implemented, is shown in Fig. 4a. The system of Fig. 4a includes an email messaging system 402, public switched telephone network (PSTN) 404 and an email recipient system 406. Email messaging system 402 includes an email server 408 and a
10 telephone dialer device 411. Email recipient system 406 typically includes notification device 116, modem 414 and computer system 416. Email server 408 is a conventional online server system with multiple user account email capability. Email server 408 may include only one server computer system, or it may include multiple, networked computer systems
15 present at one location or at several geographically separate locations. Email server 408 includes email messages 409 and telephone numbers 410, both of which are typically stored in one or more mass storage devices, such as hard disk drives.

 Dialer device 411 is connected to email server 408 and to PSTN
20 404. Device 411 receives commands and data from server 408 and transmits status and data to server 408. Device 411 is capable of initiating

telephone calls over PSTN 404 to telephone numbers received from server 408. When an email message is received by email server 408, the message is stored in email server 408 at block 409. Email server 408 then selects the telephone number corresponding to the recipient of the email message
5 from among telephone numbers 410 and transmits the selected telephone number, along with commands, to dialer device 411. A conventional modem with outdialing capability may be used as dialer device 411. However, since alert calls are terminated before connection occurs, full modem capability is not required. Thus, less expensive dial-only devices
10 may be used as dialer device 411.

An email notification process 450, implemented in the system of Fig. 4a, is shown in Fig. 4b. The process begins with step 451, in which email messaging system 402 receives an email message addressed to an email recipient registered with email messaging system 402, such as the
15 recipient at email recipient system 406. In step 452, email messaging system 402 places the received email message in the inbox corresponding to the email recipient. Typically, this inbox resides on email server 408. In step 453, email messaging system 402 places an alert call to a telephone line that has been designated by the email recipient. The alert call is
20 allowed to ring a predetermined number of times, then is terminated. In step 454, notification device 116 detects the alert call and indicates to the

email recipient that the email message is waiting. Steps 455 and 456 may be performed at the option of the recipient. In optional step 455, the email recipient may reset notification device 116. In optional step 456, the email recipient may retrieve the waiting email using system 406. The timing of the performance of steps 455 and 456, or whether the steps are performed at all, is at the option of the recipient.

Although specific embodiments of the present invention have been described, it will be understood by those of skill in the art that there are other embodiments that are equivalent to the described embodiments. Accordingly, it is to be understood that the invention is not to be limited by the specific illustrated embodiments, but only by the scope of the appended claims.

What is claimed is:

1. A method of notifying a recipient that an electronic mail message addressed to the recipient has been received at an electronic mail messaging system, comprising the steps of:

receiving an alert telephone call indicating that the electronic mail
5 message has been received at the electronic mail messaging system;

detecting the alert telephone call; and

indicating that the alert telephone call has been detected.

2. The method of claim 1, wherein the step of detecting the alert telephone call comprises the steps of:

10 detecting each ring of the telephone call; and

determining whether the telephone call is an alert call based on a number of rings of the telephone call.

3. The method of claim 1, wherein the step of indicating that the alert telephone call has been detected comprises the steps of:

15 counting a number of alert calls that have been detected; and

displaying the number of alert calls that have been detected.

4. The method of claim 3, wherein the step of detecting the alert telephone call comprises the steps of:

detecting each ring of the telephone call; and

determining whether the telephone call is an alert call based on a number of rings of the telephone call.

5. The method of claim 3, wherein the step of indicating that the alert telephone call has been detected further comprises the step of:

5 resetting the count of the number of alert calls that have been detected.

6. The method of claim 1, further comprising the step of :
resetting the indication that the alert telephone call has been detected.

10 7. The method of claim 1, wherein the alert telephone call is received from the electronic mail messaging system.

8. The method of claim 1, wherein the alert telephone call is received from a sender of the electronic mail message.

9. A method of notifying a recipient that an electronic mail message
15 addressed to the recipient has been received in an electronic mail messaging system, comprising the steps of:

receiving an electronic mail message addressed to the recipient;

initiating a telephone call to a telephone number specified by the recipient; and

20 terminating the telephone call after a predetermined number of rings.

10. An apparatus for notifying a recipient that an email message addressed to the recipient has been received, comprising:

a detection circuit capable of detecting an alert call placed in response to receipt of the email message; and

5 an indicator circuit, coupled to the detection circuit, capable of indicating that the alert call has been detected.

11. The apparatus of claim 10, wherein the indicator circuit comprises:

a counter circuit, coupled to the detection circuit, capable of counting a number of alert calls that have been detected; and

10 a display, coupled to the counter circuit, capable of displaying the number of alert calls that have been detected.

12. The apparatus of claim 11, wherein the indicator circuit further comprises:

a reset device, coupled to the counter circuit, capable of resetting
15 the number of alert calls that have been detected.

13. The apparatus of claim 10, wherein the detection circuit comprises:

a ring detector, coupled to a telephone line, capable of detecting each ring of an incoming telephone call; and

a counter/comparator circuit, coupled to the ring detector, capable
20 of determining whether the incoming telephone call is an alert call based on a number of rings of the incoming telephone call.

14. An email system comprising:

an email server capable of receiving an email message addressed to
a recipient; and

a dialer device, coupled to the email server, capable of placing an
5 alert telephone call to a telephone number specified by the recipient,
responsive to receipt of the email message by the email server.

15. The system of claim 14, wherein the dialer device places the alert
telephone call by:

initiating a telephone call to the telephone number specified by the
10 recipient;

waiting for the telephone call to ring a predetermined number of
times; and

terminating the telephone call.

16. A system for notifying a recipient of an email message, comprising:

15 an email system, capable of receiving the email message and
placing an alert telephone call to the recipient; and

a notification device, capable of receiving the alert call and
indicating receipt of the alert call to the recipient.

17. The system of claim 16, wherein the email system comprises:

20 an email server capable of receiving an email message addressed to
a recipient; and

a dialer device, coupled to the email server, capable of placing an alert telephone call to a telephone number specified by the recipient, responsive to receipt of the email message by the email server.

18. The system of claim 16, wherein the notification device comprises:

5 a detection circuit capable of outputting a signal responsive to detecting an alert call placed in response to receipt of the email message; and

an indicator circuit, coupled to the signal, capable of indicating that the alert call has been detected.

10 19. The system of claim 18, wherein the email system comprises:

an email server capable of receiving an email message addressed to a recipient; and

a dialer device, coupled to the email server, capable of placing an alert telephone call to a telephone number specified by the recipient,
15 responsive to receipt of the email message by the email server.

1/3

FIG. 1





FIG. 2



2/3

FIG. 3A




FIG. 3B




FIG. 4A

3/3





FIG. 4B



INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 98/13731

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 H04L12/58 H04M3/50

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H04L H04M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 736 989 A (ROOSTER LTD) 9 October 1996	1,3,7, 9-11, 14-19
Y	see abstract see column 2, line 48 - column 6, line 18 see column 6, line 50 - column 8, line 53 see figure 2	2,4-6, 12,13
X	--- "NO-CONNECTION SIGNAL METHOD" IBM TECHNICAL DISCLOSURE BULLETIN, vol. 32, no. 5B, 1 October 1989, page 253 XP002078948	9,14,15
Y	see the whole document	2,4,13
Y	--- WO 95 18501 A (GTE LABORATORIES INC) 6 July 1995 see page 6, line 1 - line 15 ---	5,6,12
	-/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

2 October 1998

Date of mailing of the international search report

15/10/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

RAMIREZ DE AREL..., F

INTERNATIONAL SEARCH REPORT

Intern. Application No
PCT/US 98/13731

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	<p>EP 0 508 138 A (HITACHI LTD) 14 October 1992 see abstract see column 5, line 58 - column 7, line 24 see figure 1</p> <p>-----</p>	<p>1,7,10, 14,16-19</p>

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 98/13731

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0736989	A	09-10-1996	JP 9121226 A	06-05-1997
WO 9518501	A	06-07-1995	NONE	
EP 0508138	A	14-10-1992	JP 5252198 A	28-09-1993
			US 5293250 A	08-03-1994